

WARATAH® Barb Reel Lifter

Instructions

INFORMATION: The Waratah Barb Reel Lifter is designed to be used by two people in a controlled manner. It comes pre-assembled and is rated to lift 75kg.

Note: Barbed wire pictured is not included



1. Preparing to insert jaws

Lower the Barb Reel Lifter until the jaws are near the hole in the centre of the timber reel as shown below.

Note: If lifting 1.57mm or 1.80mm High Tensile barbed wire you must pull the wire handle on the timber reel up completely to allow access with the Barb Reel lifter.



2. Inserting Jaws into timber reel

Once in position, press the jaws with one hand in the manner illustrated below to allow the jaws to enter the central hole in the timber barb spindle



3. Lift barb reel

Once the jaws have been inserted they will open up and “grab” the inside of the timber spindle. You can now proceed to lift the barb reel.



4. Walking with suspended barb wire reel

Keep your back straight when lifting and hold the handle of the Barb Reel lifter in a manner that will prevent the barb wire from swinging and making contact with your body.



5. Removing barb reel lifter from spindle once relocated.

Repeat step 2 and lift the jaws away from the timber spool.



WARATAH® Barb Reel Lifter **Instructions**

Safety

Do not exceed 75kg. Keep your back straight when lifting heavy objects. Always wear safety glasses and gloves when handling barbed wire.

Maintenance

Always maintain your Barb Reel Lifter by ensuring all bolts are tightened and all necessary parts move freely. A simple application of oil based sprays such as WD40 to all moving parts will assist in the long term performance of your Barb Reel Lifter.

The logo features the word "WARATAH" in a bold, black, sans-serif font. The text is set against a bright orange background that has a rounded, trapezoidal shape, tapering at both ends. A registered trademark symbol (®) is positioned to the upper right of the final letter "H".

WARATAH®

FIRST - BECAUSE IT LASTS.